

Product Specification

Product Class: LENS

Item No: **DK-15-12-LENS-H9**

Material: PMMA

Certification: RoHS



Content

Specification-----	3
2D Drawing-----	4
Optical Datasheet-----	5
Packing-----	6
Application Notes-----	7

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK-15-12-LENS-H9		Diameter: 15.82mm Height:8.7mm FWHM:15.2°	XPG	outdoor lamp

Drawing



Optical Test Report

产品特征

灯具制造厂商:
电压: 3.0 V
功率: 0.41 W

电流: 0.138 A
功率因数: 1.000


光度结果

灯具CIE分类: 半直接型
灯具光通量: 84.7 lm
下射光通量比: 80%
水平扩散角(50%): H15.3
垂直扩散角(50%): V15.3
灯具光效等级(LER): 206.52
峰值光强: 418.24 cd
S/MH(C0/C180): 0.27


额定光通量: 84.7 lm
灯具效率: 100%
上射光通量比: 20%

中心光强: 408.29 cd
峰值光强位置: H0 V1
S/MH(C90/C270): 0.26



灯具实物照片



配光曲线



配光曲线



Packing

Packing Material	Packing Materil size	Packing Specification
Blister box	DK-15-H86-LENS	1300PCS/inner box 24 inner box / 1 outer box
Pearl wool	120*150mm	
White paperboard	115*150mm	
Inner box	160*120*80mm	
Outer box	A=B 510*330*255mm	

Application Notes

(1) Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.

(2) Forbid to use industrial solvent to clean the lens, such as alcohol.

(3) The working temperature is $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$.

(4) Storage environment temperature is $0^{\circ}\text{C}\sim40^{\circ}\text{C}$, humidity is 30%~95%.

Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.

(5) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.

(6) Please wear gloves once install the lens, avoid to abrasion the lens surface.

(7) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.