

Product Specification

Product class: LED Streetlight

Item No.: **DK-270X75-90-TP-28H1**

Material: PC 抗 UV

Certification: RoHS

Set up: PeiShanWu

Check: JianHuaZhang


Content

Specification-----	3
2D Drawing-----	4
Optical Datasheet-----	5
Packing Details-----	6
Application Notes-----	7

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK-270X75-90-TP-28H1		Diameter: 270X75MM Height: 11.5MM FWHM: 90°	4*3030 4*2835 5050	Streetlight lens

Drawing



Optical test report

产品特征

灯具制造厂商:
电压: 43.0 V
功率: 14.80 W


电流: 0.344 A
功率因数: 1.000

光度结果


灯具CIE分类: 直接型
灯具光通量: 2456.4 lm
下射光通量比: 97%
水平扩散角(10%, 50%, 75%, 100%): H111.4, H89.4, H80.9, H63
垂直扩散角(10%, 50%, 75%, 100%): V111.1, V89.3, V80.8, V63
灯具光效等级(LER): 166.02
峰值光强: 1264.16 cd
S/MH(C0/C180): 1.57

额定光通量: 2456.4 lm
灯具效率: 100%
上射光通量比: 3%
中心光强: 1029.17 cd
峰值光强位置: H180 V29
S/MH(C90/C270): 1.55

灯具实物照片



配光曲线





平均光束角(50%): 89.3°

单位: cd

— C0-C180 — C90-C270 — G29

配光曲线



Packing Details

Material	Size	Packing Instruction
EPE	315*230mm	43PCS/1 Box 4 Box/1 Carton
Plastic bag	125*340mm	
White Paperboard	A level; 400g; 310*235mm	
Box	335*245*105mm	
Carton	A=B 510*330*255mm	



Application Notes

(1) Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.

(2) Forbid to use industrial solvent to clean the lens, such as alcohol.

(3) The working temperature is $-40^{\circ}\text{C}\sim+80^{\circ}\text{C}$ (PMMA) or $-35^{\circ}\text{C}\sim+120^{\circ}\text{C}$ (PC).

(4) Storage environment temperature is $0^{\circ}\text{C}\sim40^{\circ}\text{C}$, humidity is 30%~95%。

Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.

(5) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.

(6) Please wear gloves once install the lens, avoid to abrasion the lens surface.

(7) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.