




# Data Sheet LL04CR-BXJxxL02





# Features & Typical Applications

- High efficiency
- Available with 2 beam angles
- Optimized Uniformity
- Lens without Holder

- Highbay
- Commercial Lighting

## Table of Contents

General Information & Product Nomenclature	P.2
Optical Specifications	P.3
Mechanical Specifications	P.4
Package Specifications	P.5




# LL04CR-BXJxxL02

## General Information

- Lens Material: PC LEV1700
- Operating Temperature range -40°C~+110°C(upper limit +120°C).
- Storage Temperature range -40°C~+110°C(upper limit +120°C).
  - \* Average transmittance in visible spectrum 400nm~700nm>90%.
- Usage and Maintenance:
  - 1. If necessary, clean lenses with mild soap, water and soft cloth.
  - 2. Never use any commercial cleaning solvents on lenses, like alcohol.
  - 3. Please handle or install lenses with wearing gloves, skin oils may damage lens or its optical characteristic.

### Product Nomenclature






# LL04CR-BXJxxL02 Optical Specifications




Note: (1) All the results of analysis are based on 0 degrees of elevation.

(2) Tolerance: ±10%.

(3) Led Luminous Flux(Im): 452(±5%).





<sup>\*</sup>The Field Angle is the angle between the two directions opposed to each other over the beam axis for which the luminous intensity is 10% that of the maximum luminous intensity.
\*This testing result is obtained through testing the popular rank LED samples which provided by the original manufacturer. Hence, the testing results would be varied as the users choose same LED model but different rank.



# LL04CR-BXJxxL02 Mechanical Specification

#### 1. Fixing method

Glue

Screw

☐ Tape

Note: (1)All dimensions are in mm. (2)All tolerance are  $\pm$  0.15 mm unless otherwise specified.


☐ Fixing-ring

Frame

#### 2.Lens dimension

# Sign with different beam agins 4.20<sup>+0.20</sup> 3.00<sup>+0.20</sup> 3.00<sup>+0.20</sup> 4.20<sup>+0.20</sup> 3.00<sup>+0.20</sup> 3.00<sup>+0.15</sup> 4.20<sup>+0.20</sup> 3.00<sup>+0.15</sup> 4.20<sup>+0.20</sup> 3.00<sup>+0.15</sup> 4.20<sup>+0.20</sup> 3.00<sup>+0.15</sup> 4.20<sup>+0.20</sup> 3.00 4.20<sup>+0.15</sup> 4.20<sup>+0.20</sup> 3.00<sup>+0.15</sup> 4.20<sup>+0.15</sup> 4.20<sup></sup>

## 3. Lens + Leds assembly instruction



#### 4. Holder dimension


5. View assembly lens with LED:





# LL04CR-BXJxxL02 Package Specifications

Item	Quantity	Total	Size(L*W*H)	G.W
plastic box	30 pcs/plastic box	30 pcs	38*36*1.6 cm	
outer box	12 plastic box/outer box	360 pcs	40*37*22 cm	7.9g



	Note:					