

Lightsource Test Report



Product Information

Product Category: NEO-L-9LS2835-500
Product Spec: t=0m Ts25
Manufacturer: LUMILEDS

Product Type: L128-4080SA35A00D1
Product Number: 18

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.3768$ $y=0.3734$ $u(u')=0.2240$ $v=0.3330$ $v'=0.4996$
CCT: $T_c=4077K$ ($duv=-0.00049$) Color Ratio: $R=0.179$ $G=0.789$ $B=0.032$
Peak Wavelength: 451.0nm Half Bandwidth: 16.6nm
Dominant Wavelength: 579.1nm Color Purity: 0.252
CRI: $R_a=81.1$, $avgR(1\sim14)=73.7$, $avgR(1\sim15)=73.7$ TM30: $R_f=81$, $R_g=96$
 $R1=80$ $R2=87$ $R3=91$ $R4=81$ $R5=79$ $R6=81$ $R7=86$ $R8=64$
 $R9=5$ $R10=68$ $R11=79$ $R12=54$ $R13=81$ $R14=95$ $R15=75$
Color Quality Scale: $Q_a=80.3$, $Q_f=80.1$, $Q_p=81.4$, $Q_g=93.4$
 $Q1=82$ $Q2=98$ $Q3=74$ $Q4=71$ $Q5=78$ $Q6=81$ $Q7=83$ $Q8=88$
 $Q9=96$ $Q10=85$ $Q11=82$ $Q12=81$ $Q13=82$ $Q14=71$ $Q15=75$



Photometric Parameters

Luminous Flux: 476.13 lm
EEI: 0.06

Efficiency: 186.50 lm/W Radiant Power: 1.425 W
Energy Efficiency Class: A++ (EU 874-2012)

Electric Parameters

Voltage: 8.5100V
Power Factor: 0.0000

Current: 0.3000A Power: 2.55W
Frequency: 0.00Hz

Test Information

Scan Range: 380~800:1nm
Stabilization Time: 0 ms
Max of Signal: 46514 (1940)


Photometric Method:
Photometric Condition: Sphere diameter: 1.50m, 2PI
CCD Integration Time: 631.20 ms

IES TM-30-18 Color Rendition Report

Product Information

Product Category: NEO-L-9LS2835-500
Product Spec: t=0m Ts25
Manufacturer: LUMILEDS

Product Type: L128-4080SA35A00D1
Product Number: 18



Condition: Tx:26.8°C, Ti:25.5°C
Test Lab:
Operator:

Test Device: Lisun LMS-9000A(Plus)
Test Time: 2024-12-25 17:31:06
Inspector: