

Lightsource Test Report



Product Information

Product Category: NEO-L-9LS2835-500
Product Spec: t=0m Ts25
Manufacturer: LUMILEDS

Product Type: L128-4080SA35A00D1
Product Number: 20

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.3761$ $y=0.3723$ $u(u')=0.2240$ $v=0.3326$ $v'=0.4990$
CCT: $T_c=4090K$ ($duv=-0.00080$) Color Ratio: $R=0.179$ $G=0.789$ $B=0.032$
Peak Wavelength: 450.9nm Half Bandwidth: 17.3nm
Dominant Wavelength: 579.2nm Color Purity: 0.246
CRI: $R_a=81.2$, $avgR(1\sim14)=73.8$, $avgR(1\sim15)=73.9$ TM30: $R_f=81$, $R_g=96$
 $R1=80$ $R2=87$ $R3=91$ $R4=81$ $R5=80$ $R6=81$ $R7=86$ $R8=65$
 $R9=6$ $R10=67$ $R11=79$ $R12=55$ $R13=81$ $R14=95$ $R15=75$
Color Quality Scale: $Q_a=80.3$, $Q_f=80.1$, $Q_p=81.6$, $Q_g=93.7$
 $Q1=82$ $Q2=98$ $Q3=74$ $Q4=71$ $Q5=79$ $Q6=81$ $Q7=83$ $Q8=88$
 $Q9=96$ $Q10=85$ $Q11=81$ $Q12=81$ $Q13=82$ $Q14=71$ $Q15=75$



Photometric Parameters

Luminous Flux: 620.28 lm
EEI: 0.07

Efficiency: 177.83 lm/W Radiant Power: 1.880 W
Energy Efficiency Class: A++ (EU 874-2012)

Electric Parameters

Voltage: 8.7200V
Power Factor: 0.0000

Current: 0.4000A Power: 3.49W
Frequency: 0.00Hz

Test Information

Scan Range: 380~800:1nm
Stabilization Time: 0 ms
Max of Signal: 50386 (1961)


Photometric Method:
Photometric Condition: Sphere diameter: 1.50m, 2PI
CCD Integration Time: 536.52 ms

IES TM-30-18 Color Rendition Report

Product Information

Product Category: NEO-L-9LS2835-500
Product Spec: t=0m Ts25
Manufacturer: LUMILEDS

Product Type: L128-4080SA35A00D1
Product Number: 20



Condition: Tx:26.9°C, Ti:25.6°C
Test Lab:
Operator:

Test Device: Lisun LMS-9000A(Plus)
Test Time: 2024-12-25 17:37:45
Inspector: