



SUNSHINE ELECTRONICS TRADING LIMITED

Part No: SEL-2835-(2870-4260K)-3V300




ATTENTION

OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DISCHARGE
SENSITIVE
DEVICES


1、Features/特 征:

- Emitting Color/发光颜色: White/白色
- Lens Type/封装特性: Yellow Diffused/黄色散射
- Device Outline/外形特征: $3.5 \times 2.8 \times 0.7$ (unit:mm)
- HBM ESD:Class 2/人体抗静电指标: Class 2
- Pb-Free/无铅
- RoHS compliant/符合 RoHS 标准

2、Applications/应 用:



3、Outline Dimensions/产品外形尺寸:





SUNSHINE ELECTRONICS TRADING LIMITED

Part No: SEL-2835-(2870-4260K)-3V300

4、Absolute maximum ratings/极限参数 (Ta = 25℃):

Parameter 参数	Symbol 符号	Value 参数	Unit 单位
Power Dissipation 损耗功率	Pd	1000	mW
Reverse Voltage 反向电压	VR	7	V
Pulse Current 正向峰值电流 ^[1]	IFp	450	mA
Forward Current 正向工作电流	IFm	300	mA
Operating Temperature 工作温度范围	Topr	- 40 ~ +85	℃
Storage Temperature 储存温度范围	Tstr	- 40 ~ +100	℃
Junction Temperature 结温	Tj	115	℃

Notes/备注: [1]. 0.1ms pulse width, 1/10 Duty. / [1] 脉冲宽度0.1ms, 占空比1/10。

5、Electrical and optical characteristics/光电参数 (Ta = 25℃):

Parameter 参数	Symbol 符号	Test Condition 测试条件	Value 参数 ^[1]			Unit 单位
			Min.	Typ.	Max.	
Forward Voltage 正向电压	VF	IF = 300mA	2.9	3.2	3.4	V
Reverse Current 反向电流	IR	VR = 7V	—	—	30	μ A
Color Correlated Temperature 色温	CCT	IF = 300mA	2870	—	4260	K
Luminous Flux 光通量	Φ	IF = 300mA	—	110	—	Lm
color rendering index 显色指数	Ra	IF = 300mA	80	—	—	—
Thermal Resistance ^[2] 热阻	Rthj-s	IF = 300mA	—	30	—	℃/w
Viewing Angle 发光指向角	2θ 1/2	IF = 300mA	—	120	—	Deg.

Notes/备注: [1] Tolerance 误差: VF: ±0.10V, Φ: ±15%, 其它: ±5%; [2] Thermal Resistance is not measured value, the data is only for reference. / [2] 热阻非实测值, 数据仅供参考。



SUNSHINE ELECTRONICS TRADING LIMITED

Part No: SEL-2835-(2870-4260K)-3V300

6、Product Ranks/产品分档范围:

亮度分档标准		电压分档标准	
光通量 Φ (Lm)	代表符号	正向电压 V_F 值(V)	代表符号
IF=300mA		IF=300mA	
100-110	L100	2.90-3.00	P
110-120	L110	3.00-3.10	Q
120-130	L120	3.10-3.20	R
		3.20-3.30	S
		3.30-3.40	T

Notes/备注: Rank error/分档误差: V_F : $\pm 0.10V$, Φ : $\pm 15\%$



SUNSHINE ELECTRONICS TRADING LIMITED


Part No: SEL-2835-(2870-4260K)-3V300

色坐标分档:

色坐标误差: ± 0.005

代码	轴	参数				代码	轴	参数			
Wi3	X	0.4285	0.4362	0.4324	0.4247	Wi4	X	0.4247	0.4324	0.4286	0.4209
	Y	0.4133	0.4159	0.4074	0.4044		Y	0.4044	0.4074	0.3987	0.3957
Wi9	X	0.4362	0.4441	0.4403	0.4324	Wi10	X	0.4324	0.4403	0.4366	0.4286
	Y	0.4159	0.4187	0.4104	0.4074		Y	0.4074	0.4104	0.4018	0.3987
Wi15	X	0.4441	0.4526	0.4487	0.4403	Wi16	X	0.4403	0.4487	0.4443	0.4366
	Y	0.4187	0.4216	0.4137	0.4104		Y	0.4104	0.4137	0.4047	0.4018
Wg3	X	0.3736	0.3826	0.3799	0.3714	Wg4	X	0.3714	0.3799	0.3772	0.3692
	Y	0.3874	0.3930	0.3828	0.3775		Y	0.3775	0.3828	0.3726	0.3676
Wg8	X	0.3826	0.3916	0.3884	0.3799	Wg9	X	0.3799	0.3884	0.3853	0.3772
	Y	0.3930	0.3987	0.3881	0.3828		Y	0.3828	0.3881	0.3775	0.3726
Wg13	X	0.3916	0.4005	0.3969	0.3884	Wg14	X	0.3884	0.3969	0.3934	0.3853
	Y	0.3987	0.4044	0.3934	0.3881		Y	0.3881	0.3934	0.3825	0.3775

Diagram





SUNSHINE ELECTRONICS TRADING LIMITED

Part No: SEL-2835-(2870-4260K)-3V300

7、Typical electrical/optical characteristic curves/光电特性曲线:

Fig.1 正向电流 Vs. 正向电压




Fig.2 相对亮度 Vs. 正向电流




Fig.3 正向电流 Vs. 环境温度







Fig.4 相对亮度 Vs. 环境温度





SUNSHINE ELECTRONICS TRADING LIMITED

Part No: SEL-2835-(2870-4260K)-3V300

8、Relibility Analysis/可靠性试验

8.1 Test Items And Results/测试项目和判据

No.	Item/项目	Test Condition/测试条件	Spec. / 引用标准	Q'ty/数量	Time/时间	Standard/判定
1	IR Reflow (Reflow Soldering) 回流焊接	Tsld=220℃, 10sec	GB/T 4937, II , 2.2	20	2times	ALL PASS
2	Solder ability 可焊性	Tsld=235±5℃, 3sec	GB/T 4937, II , 2.1	20	1times Over 95%	ALL PASS
3	Temperature Cycle 高低温循环	-40℃—— 100℃ 30min ~ 30min The cut is not more than 5 min	GB/T 4937, III , 1	20	50cycles	ALL PASS
4	Moisture Resistance Cyclic 湿热循环	25℃/12hr~ 55℃/12hr 95%RH	GB/T 4937, III , 4	20	6cycles	ALL PASS
5	High Temperature Storage 高温储存	Ta=100℃	GB/T 4937, III , 2	20	1000hrs	ALL PASS
6	Low Temperature Storage 低温储存	Ta=-40℃	GB/T 4937, III , 2	20	1000hrs	ALL PASS
7	Steady State perating Life 电耐久性	IF=300mA Ta=25℃	GB/T 18904.3 Part A	20	1000hrs	ALL PASS

8.2 Criteria For Judging Damage/判断标准

Item/项目	Symbol/ 符号	Test conditions /测试条件	Criteria for Judgement /判断标准	
			Min./最小值	Max./最大值
Luminous Intensity/亮度	Iv	IF=300mA	L.S.L *0.7	/
Forward Voltage/正向电压	VF	IF=300mA	/	U.S.L*1.1
Reverse current/反向电流	IR	VR=7v	/	U.S.L*2

*U.S.L.: Upper Standard Level / 上限

*L.S.L.: Lower Standard Level / 下限



SUNSHINE ELECTRONICS TRADING LIMITED


Part No: SEL-2835-(2870-4260K)-3V300

9、Specification of Packing /包装规格

9.1 Taping and Orientation /编带和方向

Quantity/数量 : 3000units/reel

Diameter/直径 : 178 mm



Item/项目	Spec/数值	Tol.(+/-)/误差	Item/项目	Spec/数值	Tol.(+/-)/误差
W	8.00	± 0.10	P2	2.00	± 0.05
E	1.75	± 0.10	T	0.20	± 0.02
F	3.50	± 0.010	A0	3.00	± 0.10
D0	1.55	± 0.05	B0	3.75	± 0.10
D1	1.10	± 0.1	K0	1.25	± 0.10
P0	4.00	± 0.1	α	Max 5°	