

SAMSUNG

Samsung LED Business

May 2020

LED Business Division – Lighting

Samsung Electronics / Samsung Semiconductor Europe GmbH





16552233

SAMSUNG


Product update

Efficacy

Leading Efficacy in All Products



CRI 90 with High Efficacy (LM301B)




Reliability

Better Mechanical Strength


HPL LH351B

- Carefully Controlled Surface Material



HPL 351B

- Higher Lens Peel Strength



LH351B
1.52Kg




Company A
1.22Kg

Better Corrosion Resistance


MPL LM301B

- High Reflectance without Ag Metal exposure



MPL 301B

- Lower Lumen Degradation in Harsh Environment



※ H2S 15ppm, 25°C / 75% humidity for 504hrs

Better Reliability in Entry Level

MPL LM281B+ PRO

- Advanced Wire Loop and thicker wire



Thermal Cycle
200 → 500

- New Phosphor Process



WHTOL (85C, 85%)
85% → 90%

- Anti Sulfur Protective Coating



Anti H2S Corrosion
88% → 92%

Innovation

Circadian Lighting

MPL LM302N


Enhancing circadian rhythm
synchronization with
melanopic spectrum



Horticultural Lighting

MPL LM301H, LM561C, LH351H

Improving the plant growth
with high PPF/W spectrum



IoT Module

Dual wireless protocol
BLE 5.0 & Zigbee 3.0
controlled via the SmartThings



SAMSUNG


MPL packages

MPL Position review

3030 (Indoor & Outdoor) , 5630 (Workhorse) , 2835 (Value)


Builds up the 3030 full line-up & reliability improved 2835 ('19.3Q)

LM301B provides the world best performance (225lm/W@5000K)



3030 Positioning

Keep leadership in efficacy evolution for LM301B



Samsung 3030 Product & Target Application


3V

LM301B



TiO₂ Reflector

LM301Z+




New: Protection Layer against H₂S

NEW LM301D




6V

LM302Z+



New: Protection Layer against H₂S

NEW LM302D



. Linear /Area/Indoor




Indoor(Ambient) lighting



. High-bay/Flood/Outdoor



Industrial lighting



3030 Product

World Highest Efficacy_ LM301B


Designed for best efficacy products

Key Features

- 0.2W, 3V mid power LED
- Performance: 220lm/W (@65mA, 4000K, Ra80+)
- Anti-sulfurization - No Silver Exposure (Sulfurization free)
- Standard footprint with $3.0 \times 3.0 \text{ mm}^2$
- LM80 Certified @200mA, 105°C (Ts)
(L70 > 100,000 @150mA, 105°C)

Product Availability

CRI	CCT						
	2700K	3000K	3500K	4000K	5000K	5700K	6500K
70+	-	0	0	0	0	-	-
80+	0	0	0	0	0	0	0
90+	0	0	0	0	0	0	0



Footprint $3.0 \times 3.0 \text{ mm}$

Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LM301B	Available	Available	Available	Available

3030 Product

New Product _ LM301D


Designed for best lm/\$ for Ambient, Down light

Key Features

- 0.2W, 3V mid power LED
- Performance: 207lm/W (@65mA, 4000K, Ra80+)
- Providing Single flux range & single Vf
- Standard footprint with 3.0 × 3.0 mm²
- EMC lead frame material with high reliability
- Anti-sulfurization

Product Availability

CRI	CCT						
	2700K	3000K	3500K	4000K	5000K	5700K	6500K
70 ⁺	-	0	0	0	0	-	-
80 ⁺	0	0	0	0	0	0	0
90 ⁺	0	0	0	0	0	0	0



Footprint 3.0 × 3.0 mm

- Identical Pad Design for market compatibility

Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LM301D	Available	Available	Available	Available

3030 Product

New Product _ LM302D


Designed for best lm/\$ for Ambient, Industrial lighting

Key Features

- 0.9W, 6V mid power LED
- Performance: 160lm/W (@150mA, 4000K, Ra80+)
- [Providing Single flux range](#)
- Standard footprint with 3.0 × 3.0 mm²
- EMC lead frame material with high reliability
- [Anti-sulfurization](#)

Product Availability

CRI	CCT						
	2700K	3000K	3500K	4000K	5000K	5700K	6500K
70+	-	May.'20	May.'20	May.'20	May.'20	-	-
80+	O	O	O	O	O	O	O
90+	O	O	O	O	O	O	O



Footprint 3.0 × 3.0 mm

- Identical Pad Design for market compatibility

Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LM302D	Available	Available	Available	Available

3030 Product

LM301Z+


Designed for best lm/\$ for Ambient, Down light

Key Features

- 0.2W, 3V mid power LED
- Performance: 196lm/W (@65mA, 4000K, Ra80+)
- [Providing Single flux range](#)
- Standard footprint with 3.0 × 3.0 mm²
- [EMC lead frame](#) material with high reliability
- [Anti-sulfurization](#)

Product Availability

CRI	CCT						
	2700K	3000K	3500K	4000K	5000K	5700K	6500K
70 ⁺	-	0	0	0	0	-	-
80 ⁺	0	0	0	0	0	0	0
90 ⁺	0	0	0	0	0	0	0



Footprint 3.0 × 3.0 mm

- Identical Pad Design for market compatibility

Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LM301Z+	Available	Available	Available	Available

3030 Product

LM302Z+


Designed for best lm/\$ for Ambient, Industrial lighting

Key Features

- 0.9W, 6V mid power LED
- Performance: 155lm/W (@150mA, 4000K, Ra80+)
- Providing Single flux range
- Standard footprint with 3.0 × 3.0 mm²
- EMC lead frame material with high reliability
- Anti-sulfurization

Product Availability

CRI	CCT						
	2700K	3000K	3500K	4000K	5000K	5700K	6500K
70+	-	0	0	0	0	-	-
80+	0	0	0	0	0	0	0
90+	0	0	0	0	0	0	0



Footprint 3.0 × 3.0 mm

- Identical Pad Design for market compatibility


Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LM301Z+	Available	Available	Available	Available

3030 Updates

Uploading new information of LM302Z+ Eco (LM302Z+ Zenerless version)

Economic and Eco-friendly



LM302Z+

- 0.9 W, 6 V mid power LED
- Luminous Flux: 139 lm @ 150 mA
- Luminous Efficacy: 150 lm/W

LEARN MORE

Tech Spec

Wattage
0.9 W

Forward Voltage
6.2 V

LM302Z+
139 lm, 150 lm/W

Condition
5000K, 150 mA, 25°C

LM302Z+ Eco
143 lm, 155 lm/W

Documentation

Data Sheets	Application Notes	Design Files	Product Ecology	Brochures	
[Data Sheet] LM302Z+ CRI 70			v2.3	2020-04-23	DOWNLOAD 
[Data Sheet] LM302Z+ CRI 80			v2.3	2020-04-23	DOWNLOAD 
[Data Sheet] LM302Z+ CRI 90			v2.3	2020-04-23	DOWNLOAD 
[Data Sheet] LM302Z+ Eco CRI 70			v1.3	2020-04-23	DOWNLOAD 
[Data Sheet] LM302Z+ Eco CRI 80			v1.3	2020-04-23	DOWNLOAD 

Line-up

New Product _ LM281B+ Pro

Builds up the reliability improved 2835 for mainstream applications

Key Features

- 0.5W, 3V mid power LED
- Standard footprint with $2.8 \times 3.5 \text{ mm}^2$
- LM80 Certified @200mA, 105°C (Ts)



Footprint $2.8 \times 3.5 \text{ mm}$

- Identical Pad Design for market compatibility



80~85lm
@150mA

Product Availability

Model	CRI	CCT (2700~6500K)		
		VG rank	VJ rank	VK rank
LM281B+ Pro	80+	Available		
	90+			
LM281B+ Pro + Zener	80+			
	90+			

Sampling & Launching Schedule

Model	Sample	Data sheet	MP	LM80
	Approval	Final		
LM281B+ PRO	Available	Available	Available	Available

Performance(Lumen)

Model	Sorting Current	Rank	CCT	Lumen[Lm]	
				Min.	Max.
281B+ Pro. CRI80	150mA	VG	2700K	66.5	70.5
			5000K	73.0	77.0
		VJ	2700K	70.5	74.5
			5000K	77.0	81.0
	65mA	VK	2700K	32.5	34.5
			5000K	35.5	37.5

Performance Improvement


LM281B+ PRO - Upgraded Reliability Brings Higher Value

Thermal Cycle

-45°C ~125 each 15min, transition time 5sec

With advanced loop, guarantee 500 cycle

T/C Test



Advanced loop

Top view




Side view



WHTOL(85%,85C)

85°C/85%@200mA, 1000hrs

Improved WHTOL reliability





2835

2835 PRO

Concept




Image



Anti sulfurization

H₂S 15ppm 25°C/75%, 504hrs



Improved corrosion performance



2835

2835 PRO


Concept



2835 3V Standard Line-up

Competitive 3V line-up → RG/RJ/RK

2835 3V Line-up & Performance



RG, RJ & RK Specification comparison

LM281B+ SG / **RG** rank - MP

Nominal CCT (K)	Bin	Ra	Vf (typ)	150mA (IF _{op})	
				Min.	Max.
4000	SG	80	2.95	72	76
	RG		2.97	72	76

LM281B+ SJ / **RJ** rank

Nominal CCT (K)	Bin	Ra	Vf (typ)	150mA (IF _{op})	
				Min.	Max.
4000	SJ/RJ	80	2.95	76.0	80.0

LM281B+ SK / **RK** rank - MP

Nominal CCT (K)	Bin	Ra	Vf (typ)	65mA (IF _{op})	
				Min.	Max.
4000	SK	80	2.74	35.5	37.5
	RK		2.74	35.0	37.0

SAMSUNG


High Power

Samsung Ceramic 3535 Series


Easy to extend line-up

Greater design flexibility for various fixture designs with same footprint, chip and phosphor technology



- Same Size



- Same Footprint




- Same Chip & Phosphor Technology



* PCB: Printed Circuit Board


LH351B/C/D – Performance




H₂S Sulfurization Test - Safe

Product	Range	Lumen Maintenance(%)	
		0 h	504 h
LH351B	Min.	100.00%	93.1%
	Max.	100.00%	100.1%
	Avg.	100.00%	97.5%
LH351C	Min.	100.00%	99.53%
	Max.	100.00%	101.26%
	Avg.	100.00%	99.97%
LH351D	Min.	100.00%	97.04%
	Max.	100.00%	102.23%
	Avg.	100.00%	99.66%


Product	Range	Chromaticity Shift($\Delta u'v'$)	
		0 h	504 h
LH351B	Min.	0.0000	0.0001
	Max.	0.0000	0.0015
	Avg.	0.0000	0.0003
LH351C	Min.	0.0000	0.0004
	Max.	0.0000	0.0006
	Avg.	0.0000	0.0005
LH351D	Min.	0.0000	0.0004
	Max.	0.0000	0.0024
	Avg.	0.0000	0.0014



[Top View]



[Cross Section View]



Hydrogen Sulphide

- Ambient Temperature : 25 °C
- Relative Humidity : 75%
- H₂S concentration : 15 ppm
- Applicable Standards : IEC 60068-2-43

More than 95% of Ag doesn't effect on light path

Samsung 5050 New Solution

New Product _ LH508C (24V) / LH502C (6V)

5050 Highest lm/W in the world

Key Features

- approximately 8% Spec up than 508A+
220lm/W @ 1W (4000K, CRI70, Tj=25°C)
230lm/W @ 0.5W (4000K, CRI70, Tj=25°C)
- Max current : 220mA (24V) / 880mA (6V), Tj=125°C
- Anti Sulfurization
- Improved Color quality
- Keep exterior with LH508A+



Dimension : 5.0 × 5.0 mm


Product Availability

	CRI	CCT						
		2200K	2700K	3000K	4000K	5000K	5700K	6500K
502C	70	tbd	End May '20				End Jul '20	
	80	tbd	End May '20				End Jul '20	
508C	70	tbd	End May '20				End Jul '20	
	80	tbd	End Jun '20				End Jul '20	

Sampling & Launching Schedule

	Sample	Data sheet	MP	LM80
	Approval	Final		
LH502C	<CRI70> May '20 <CRI80> Jun '20	End May '20	Jun '20	End Jun '20
LH508C	<CRI70> Jun '20 <CRI80> End Jun '20	End May '20	Jun '20	End Jun '20

Package Platforms for Outdoor Applications



	Im/W	Im/\$	Im/Area	Thermal Management	Lifespan
Ceramic	●●	●	●●	●●	●●●
CSP	●●	●●	●●●	●●●	●●●
EMC	●●●	●●●	●	●	●●

CSP


SAMSUNG

History & Why SAMSUNG CSP

CSP was generated for requirement of small LES & simple structure.


- Depended on world best flip-chip technology from SAMSUNG.

SAMSUNG secured stable technology of CSP during last 5 years.



FEC CSP Line-up

FEC CSP Structure



Lineup

Category	LM101B (1W, 3V)	LH151B (2W, 3V)	LH181B (3W, 3V)	LH231B (5W, 3V)
Appearance		 <i>New to come</i>		
Dimension (W × L × H, mm)	1.7 × 1.7 × 0.34	1.7 × 1.7 × 0.34	2.36 × 2.36 × 0.35	2.80 × 2.80 × 0.35
Max Current	350mA	700mA	1400mA	2000mA
Sorting Condition	150mA, 85°C	350mA, 85°C	350mA, 85°C	700mA, 85°C

COB


SAMSUNG

COB lineup




R-series with Specialized Spectrum


Fashion Vivid Color




Fashion Vivid White



Meat



Vegetable



NEW: up to 1 SDCM Product Line-up

COB D-series Platform	CCT (K)		2700	3000	3500	4000	5000	5700	6500	Performance (LC026D)
Gen.3	CRI 70+	Before		3step		3step	3step			D3 rank: 161lm/W
		New		2step		2step	2step			
	CRI 80+	Before	3step/2step	3step/2step	3step/2step	3step/2step	3step	3step	3step	
		New	1step	1step	1step	1step	2step	2step	2step	
	CRI 90+	Before	3step/2step	3step/2step	3step/2step	3step/2step	3step			
		New	1step	1step	1step	1step	1step			
Gen.2	CRI 70+	Before		3step		3step	3step			D2 rank: 151lm/W
		New		2step		2step	2step			
	CRI 80+	Before	3step/2step	3step/2step	3step/2step	3step/2step	3step	3step	3step	
		New	1step	1step	1step	1step	2step	2step	2step	
	CRI 90+	Before	3step/2step	3step/2step	3step/2step	3step/2step	3step			
		New	1step	1step	1step	1step	2step			
	CRI 95+	Before	3step/2step	3step/2step	3step/2step	3step/2step	3step			
		New	1step	1step	1step	1step	2step			

SAMSUNG




T-series

Wide range of color temperature

T-series with Tunability







CRI90 available
2700~5000K

Tunable COB Design/lineup

	LC010T	LC020T	LC035T
Concept Image			
PKG size	19x19 mm ²	19x19 mm ²	28x28 mm ²
LES size	9.8 mm	13.0 mm	22.0 mm
No. of Chips/CSPs	12/12	24/24	48/48
If / Vf	280 mA / 35 V	560 mA / 35 V	980 mA / 35 V
Flux(@6500K, CRI80)	1313 lm	2626 lm	4802 lm
Efficacy (@6500K, CRI80)	134 lm/W	134 lm/W	140 lm/W

T-series with Tunability

Excellent color uniformity with concentric chip arrangement

Company	Samsung	Competitor A	Competitor B
PKG / Chip layout			
Chip layout type / Characteristic	Concentric Circle (CSP + DP) Round Dam	Lattice arrangement (CSP + DP) Octagonal Dam	Lattice arrangement (CSP only) No Dam
CCT Distribution (Simulation)			
STD(CCT)	42	105	146

Human-centric Lighting Solution


Melanopic Spectrum

SAMSUNG



The Non-visual Effects of Light


Light-dark cycle entrains the circadian rhythms through neuroendocrine pathway



* ipRGCs: intrinsically photosensitive Retinal Ganglion Cells


Light Sensitivity of Circadian System

Retinal phototransduction with melanopic sensitivity located around 480nm entrains the circadian rhythm by producing pineal melatonin




Fine-Tuned Spectra for Advanced Circadian Lighting

Dedicated Daytime
Spectrum




High M/P Ratio

Standard LED
Spectrum



Dedicated Nighttime
Spectrum




Low M/P Ratio

SAMSUNG

Topic / Author / Date

LM302N Melatonin suppression performance



[Graph generated by the tool from Lighting Research Center (LRC), RPI]

*Luminous flux indoors 150lux ≤ 3000K, 400lux ≥ 3500K

The melatonin control performance of Samsung Circadian Lighting is relatively 20%~30% higher than that of Normal LED in overall CCTs.



SAMSUNG

Horticulture Lighting Solution




Full Spectrum LED

Full spectrum is recent trend with more cost-effective, productive, and favorable solution



More Productive Solution


Full spectrum promotes balanced plant growth by improving many different aspects



Why Samsung LED


Samsung Horticultural LED line-up is formed with the key considerations in mind

Freedom in Spectrum



Spectrum of infinite possibilities
enabling purpose driven plant growth

Industry Leading PPF/W



The highest efficacy increasing yield
of crops and saving operation cost

Enhanced Quality




Industry proven reliability under
harsh horticulture environment

High Sulfur Environment

LEDs can be degraded by sulfur in horticulture application



Conventional Package




- Ag in wire or electrodes can be tarnished when exposed to H_2S
- $2Ag + H_2S + 1/2O_2 \rightarrow Ag_2S + H_2O$ (Ag_2S causes PPF degradation)


Superior Sulfur Resistance

LEDs with protection schemes are necessary to maintain PPF, Spectrum, etc.

Horticulture LEDs with Protection Schemes






H₂S 15ppm, 25°C / 75% humidity for 504hrs



※ IEC Pub.68-2-43

More Options for Customer Choice

High Efficacy : LM301H + LH351H Red, Easy Use : LM301H ONE

High Efficacy		Easy Use
LM301H	LH351H Deep Red	LM301H ONE (1 PKG Solution)
		
- High PPF/W - Flexible spectrum design		- Simple module/lens design - Easy SMT and SKU management - More uniform light distribution - Spectrum based on experiment
		

SAMSUNG

Topic / Author / Date

Page 47

Product Lineup

White LED (MPL)

3030 white LEDs deliver the highest efficacy and excellent reliability

LM301H



Key Features

- 0.2W, 3V mid power LED
- World's best efficacy
- Anti-sulfurization
- Standard footprint with 3.0 × 3.0 mm²

Rank	Color	PPF (μmol/s)	Efficacy (μmol/J)
SL	White	0.56	3.10

@65mA, 25°C, 6500K, CRI80

LM301H ONE




Key Features

- 0.2W, 3V mid power LED
- 1 PKG solution with optimized spectrum
- Anti-sulfurization
- Standard footprint with 3.0 × 3.0 mm²

Rank	Color	PPF (μmol/s)	Efficacy (μmol/J)
(TBA)	White	(TBA)	(TBA)

@65mA, 25°C, 6500K, CRI80



	Ref	ONE
R:G:B	1:4:4	1:8:6
CCT	3000	3800
CRI	80	73
CIE x	0.4386	0.4218
CIE y	0.4116	0.4944

Vertical / Indoor Farming Solution



- Crop: Lettuce, Herb, etc.
- LED Lighting Requirements: Efficacy $\uparrow$, Thermal Management

	White LED			Color LED				
								
	LM301H	LM561H	LM301H ONE	LH351H Blue (450nm)	LH351H Red (630nm)	LH351H Deep Red (660nm)	LH351H Deep Red (660nm) V2	LH351H Far Red (730nm)
PPF ($\mu\text{mol/s}$)	0.56	0.51	0.49	2.80	1.57	2.32	2.63	*1.96
PPF/W ($\mu\text{mol/J}$)	3.10	2.84	2.75	2.80	2.14	3.12	3.73	**2.91
Footprint (mm^2)	3.0 $\times$ 3.0	5.6 $\times$ 3.0	3.0 $\times$ 3.0	3.5 $\times$ 3.5				

*BPF, **BPF/W

Greenhouse Farming Solution

- Crop: Tomato, Pepper, Cucumber, etc.
- LED Lighting Requirements: Cost↓, Size/Weight↓

	White LED					Color LED				
										
	LH241H	LH281H	LH351H-B	LH351H-C	LH351H-D	LH351H Blue (450nm)	LH351H Red (630nm)	LH351H Deep Red (660nm)	LH351H Deep Red (660nm) V2	LH351H Far Red (730nm)
PPF (μmol/s)	2.51	2.59	2.48	2.56	2.58	2.80	1.57	2.32	2.63	*1.96
PPF/W (μmol/J)	2.52	2.65	2.51	2.60	2.69	2.80	2.14	3.12	3.73	**2.91
Footprint (mm ²)	2.4 × 2.4	2.8 × 2.8	3.5 × 3.5			3.5 × 3.5				

*BPF, **BPF/W

Main Applications

Vertical/Indoor Farming



* Crop: Lettuce, Herb → Short Size, Short Life Cycle
 * LED Requirements: High Efficacy, Thermal Dissipation↓, Cost↓

Greenhouse Farming



* Crop: Tomato, Pepper, Cucumber → Tall Size
 * LED Requirements: High power, Size↓, Weight↓

SAMSUNG

Thank You